

Model : DKA15C-12 15W
 V1 : +12V / 62.5~625mA
 V2 : - 12V / 62.5~625mA

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	OUTPUT VOLTAGE ACCURACY	-2%~+2%	I/P: 48VDC O/P:50% LOAD Ta:25°C	V1:+1.27 % V2:+1.14 %	P
2	RIPPLE & NOISE	60mVp-p	I/P:48VDC O/P:FULL LOAD Ta:25°C	V1:15 mVp-p V2:13 mVp-p	P
3	LINE REGULATION	-0.2%~+0.2%	I/P:36VDC ~72VDC O/P:FULL LOAD Ta:25°C	V1:-0.03 %~ -0.03 % V2:+0.00 %~ -0.01%	P
4	LOAD REGULATION	-0.5%~+0.5%	I/P:48VDC O/P: MIN ~FULL LOAD Ta:25°C	V1:+0.04 %~ -0.13% V2:-0.04%~ +0.14%	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	36VDC~72VDC	I/P:TESTING O/P:FULL LOAD Ta:25°C	31.85V~72Vdc	P
2	EFFICIENCY	82% (Typ)	I/P:48VDC O/P:FULL LOAD Ta:25°C	83.92%	P
3	INPUT CURRENT	400mA FULL LOAD (Max.) 15mA NO LOAD (Typ.)	I/P:48VDC O/P:TEST Ta:25°C	375 mA / FULL LOAD 6.1 mA / NO LOAD	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	110%~250%(Typ)	I/P:48VDC O/P:TESTING Ta:25°C	152.0% HICCUP MODE AUTO-RECOVER	P
2	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P:36VDC O/P:FULL LOAD Ta:25°C	NO DAMAGE HICCUP MODE AUTO-RECOVER	P



SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P:1000 VDC/min	I/P-O/P:1000 VDC/min Ta:25°C	I/P-O/P: 0.02mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P:500 VDC Ta:25°C	I/P-O/P>100MΩ NO DAMAGE	P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2008.1.9	STOCK	PASS	PETER	T.K.CHENG