



MODEL : NSD10-12D5

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1: 75 mVp-p (Max) V2: 75 mVp-p (Max)	I/P: 12VDC O/P:FULL LOAD Ta:25°C	V1: 20 mVp-p (Max) V2: 12 mVp-p (Max)	P
2	OUTPUT VOLTAGE TOLERANCE	V1: 4 %- -4 % (Max) V2: 4 %- -4 % (Max)	I/P: 9.8VDC / 36VDC O/P:FULL/ MIN LOAD Ta:25°C	V1: 1.9 %- -1.9 % V2: 2 %- -2 %	P
3	LINE REGULATION	V1: 1%- -1 % (Max) V2: 1%- -1% (Max)	I/P: 9.8VDC ~ 36VDC O/P:FULL LOAD Ta:25°C	V1: 0 %- 0 % V2: 0 %- 0 %	P
4	LOAD REGULATION	V1: 3 %- -3 % (Max) V2: 3 %- -3 % (Max)	I/P: 12VDC O/P:FULL -MIN LOAD Ta:25°C	V1: 0 %- 0 % V2: 0 %- 0 %	P
5	CROSS REGULATION	V1: 3 %- -3 % (Max) V2: 3 %- -3 % (Max)	I/P: 12V VDC O/P: Testing O/P 60%LOAD Other O/P 40%LOAD Change Ta:25°C	V1: 1.5 %- -1.5 % V2: 1.4 %- -1.4 %	P
6	OVER/UNDERSHOOT TEST	< ±5%	I/P: 12 VDC O/P:FULL LOAD Ta:25°C	TEST: < 5 %	P
7	DYNAMIC LOAD	V1: 1000 mVp-p	I/P: 12VDC O/P:FULL /Min LOAD 90%DUTY/1KHZ Ta:25°C	193 mVp-p	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	9.8VDC~ 36 VDC	I/P:TESTING O/P:FULL LOAD Ta:25°C	8.7 V~36 V	P
			I/P: LOW-LINE-0.2V= 9.6 V HIGH-LINE+5%= 37.8 V O/P:FULL/MIN LOAD ON: 30 Sec . OFF: 30 Sec 10MIN (AC POWER ON/OFF NO DAMAGE)	TEST: OK	
2	EFFICIENCY	76 % (TYP)	I/P: 12 VDC O/P:FULL LOAD Ta:25°C	76.5 %	P
3	INPUT CURRENT	12 VDC/ 1.4A(TYP)	I/P: 12 VDC O/P:FULL LOAD Ta:25°C	I = 1.06 A	P
4	SHUTDOWN IDLE CURRENT	20 mA / 12VDC	I/P: 12 VDC O/P:FULL LOAD Ta:25°C	18.1 mA / 12VDC	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	Above 105%	I/P: 12VDC O/P: TESTING Ta: 25°C	146 % / 12V Over power Limiting, recovers automatically after fault condition is removed	P
2	OVER VOLTAGE PROTECTION	CH1: 5.75 V~ 7.5V CH2: -5.75 V~ -7.5V	I/P: DC SOURCE O/P: MIN LOAD Ta: 25°C	6.1 V / CH1 / 0.17A 6.1 V / CH2 / 0.17A Recovers automatically after fault condition is removed	P
4	SHORT PROTECTION	SHORT EVERY OUTPUT 60 SECOND NO DAMAGE	I/P: 36 VDC O/P: FULL LOAD Ta: 25°C	NO DAMAGE Constant Current Limiting	P

CONTROL FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	REMOTE CONTROL	Logic "1" OPEN : ON Logic "0" GON : OFF	I/P: 12VDC O/P: FULL LOAD Ta: 25°C	Logic "1" : POWER ON Logic "0" : POWER OFF	P

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT																																																												
1	TEMPERATURE RISE TEST	MODEL : NSD10-12D5 1. ROOM AMBIENT BURN-IN : 1.5 HRS I/P: 12 VDC O/P: FULL LOAD Ta= 25.1℃ 2. HIGH AMBIENT BURN-IN : 2HRS I/P: 12 VDC O/P: FULL LOAD Ta= 58.2 ℃			P																																																												
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>P/N</th> <th>ROOM AMBIENT Ta= 25.1 ℃</th> <th>HIGH AMBIENT Ta= 58.2 ℃</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>D100</td> <td>SR-26 2A/60V</td> <td>77.8℃</td> <td>108.7℃</td> </tr> <tr> <td>2</td> <td>D200</td> <td>SR-26 2A/60V</td> <td>61.1℃</td> <td>91.8℃</td> </tr> <tr> <td>3</td> <td>L100</td> <td>TS-027</td> <td>69.3℃</td> <td>103.1℃</td> </tr> <tr> <td>4</td> <td>C106</td> <td>33U/10V 125℃</td> <td>68.0℃</td> <td>98.8℃</td> </tr> <tr> <td>5</td> <td>C5</td> <td>105/50V 125℃</td> <td>69.9℃</td> <td>101.2℃</td> </tr> <tr> <td>6</td> <td>T1 COIL</td> <td>TS-015</td> <td>79.5℃</td> <td>112.0℃</td> </tr> <tr> <td>7</td> <td>Q1</td> <td>BCX56 1A/80V</td> <td>70.0℃</td> <td>101.2℃</td> </tr> <tr> <td>8</td> <td>Q2</td> <td>CET1012 10A/120V</td> <td>73.4℃</td> <td>105.5℃</td> </tr> <tr> <td>9</td> <td>L1</td> <td>1UH</td> <td>69.4℃</td> <td>100.9℃</td> </tr> <tr> <td>10</td> <td>U1</td> <td>TL3843</td> <td>76.4℃</td> <td>107.7℃</td> </tr> <tr> <td>11</td> <td>CASE</td> <td>上方中間處</td> <td>68.4℃</td> <td>99.6℃</td> </tr> </tbody> </table>	NO	Position		P/N	ROOM AMBIENT Ta= 25.1 ℃	HIGH AMBIENT Ta= 58.2 ℃	1	D100	SR-26 2A/60V	77.8℃	108.7℃	2	D200	SR-26 2A/60V	61.1℃	91.8℃	3	L100	TS-027	69.3℃	103.1℃	4	C106	33U/10V 125℃	68.0℃	98.8℃	5	C5	105/50V 125℃	69.9℃	101.2℃	6	T1 COIL	TS-015	79.5℃	112.0℃	7	Q1	BCX56 1A/80V	70.0℃	101.2℃	8	Q2	CET1012 10A/120V	73.4℃	105.5℃	9	L1	1UH	69.4℃	100.9℃	10	U1	TL3843	76.4℃	107.7℃	11	CASE	上方中間處	68.4℃	99.6℃		
NO	Position	P/N	ROOM AMBIENT Ta= 25.1 ℃	HIGH AMBIENT Ta= 58.2 ℃																																																													
1	D100	SR-26 2A/60V	77.8℃	108.7℃																																																													
2	D200	SR-26 2A/60V	61.1℃	91.8℃																																																													
3	L100	TS-027	69.3℃	103.1℃																																																													
4	C106	33U/10V 125℃	68.0℃	98.8℃																																																													
5	C5	105/50V 125℃	69.9℃	101.2℃																																																													
6	T1 COIL	TS-015	79.5℃	112.0℃																																																													
7	Q1	BCX56 1A/80V	70.0℃	101.2℃																																																													
8	Q2	CET1012 10A/120V	73.4℃	105.5℃																																																													
9	L1	1UH	69.4℃	100.9℃																																																													
10	U1	TL3843	76.4℃	107.7℃																																																													
11	CASE	上方中間處	68.4℃	99.6℃																																																													
2	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR (MIN)	I/P: 12VDC O/P: 120 % LOAD Ta:25℃	TEST : OK	P																																																												
3	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P: 12 VDC O/P: 100 % LOAD Ta= -25℃	TEST : OK	P																																																												
4	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 60 ℃ NO DAMAGE	I/P: 39 VDC O/P:FULL LOAD Ta= 60℃ HUMIDITY= 95 %R.H	TEST : OK	P																																																												
5	TEMPERATURE COEFFICIENT	± 0.03 %(0-60℃)	I/P: 12 VDC O/P:FULL LOAD	± 0.006 %(0-60℃)	P																																																												
6	VIBRATION TEST	1 Carton & 1 Set (1) Waveform: Sine Wave (2) Frequency:10-500Hz (3) Sweep Time:10min/sweep cycle (4) Acceleration:2G (5) Test Time:1 hour in each axis (X.Y.Z) (6) Ta:25℃		TEST : OK	P																																																												

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P: 1.5KVDC/min	I/P-O/P: 1.8KVDC/min Ta:25℃	I/P-O/P: 0.002 mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P: 500 VDC Ta:25℃ / 70% RH	I/P-O/P: 30 GΩ NO DAMAGE	P
3	APPROVAL	TUV: Certificate NO : UL: File NO : E183223			P



E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RADIATION	EN55022 CLASS B	I/P: 12VDC O/P: FULL LOAD Ta: 25°C	PASS Test by certified Lab	P
2	E.S.D	EN61000-4-2 LIGHT INDUSTRY AIR: 8KV / Contact: 4KV	I/P: 12 VDC O/P: FULL LOAD Ta: 25°C	CRITERIA A	P
3	E.F.T	EN61000-4-4 LIGHT INDUSTRY INPUT: 1KV	I/P: 12 VDC O/P: FULL LOAD Ta: 25°C	CRITERIA A	P
7	Test by certified Lab & Test Report Prepare				

M.T.B.F & LIFE CYCLE CALCULATION

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	MTBF	MIL-HDBK-217F NOTICES2 PARTS COUNT TOTAL FAILURE RATE: 1878.5K HRS			P

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor (D to S) or (C to E) Peak Voltage	Q2 Rated CUE1012 : 120 V 10 A	I/P: High-Line +3V = 39 V O/P: (1) Full Load Turn on (2) Output Short Ta: 25°C	(1) 71 V (2) 81 V	P
2	Diode Peak Voltage	D100 Rated SR26 : 60V 2 A D200 Rated SR26 : 60V 2 A	I/P: High-Line +3V = 39 V O/P: (1) Full Load Turn on (2) Output Short Ta: 25°C	(1) 53 V (2) 32 V (1) 54 V (2) 33 V	P
3	Input Capacitor Voltage	C5 Rated : 105 / 50V	I/P: High-Line +3V = 39 V O/P: (1) Full Load Turn on /Off (2) Min load Turn on /Off (3) Full Load /Min load Change Ta: 25°C	(1) 38.99 V (2) 39.03 V (3) 39.03 V	P
4	Control IC Voltage Test	U1 Rated TL3843D : 20 V	I/P: High-Line +3V = 39 V O/P: (1) Full Load Turn on /Off (2) Min load Turn on /Off (3) Full Load /Min load Change Ta: 25°C	(1) 14.89 V (2) 11.59 V (3) 14.89 V	P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2007/1/11	RD SAMPLE	PASS	VINCENT TSENG	MAX LIN
2007/3/5	PRODUCT SAMPLE W0702A48	PASS	VINCENT TSENG	MAX LIN
2007/5/24	PRODUCT SAMPLE W0705B71	PASS	VINCENT TSENG	MAX LIN

2003/12/12 A50-F023