

Model : SKE15C-15 15W DC-DC Single Output Converter
 V1 : +15V / 100~1000mA

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	VOLTAGE ACCURACY	-2%~+2% (Max)	I/P:48VDC O/P:50% LOAD Ta:25°C	-0.7%	P
2	RIPPLE & NOISE	60mVp-p (Max)	I/P:48VDC O/P:FULL LOAD Ta:25°C	13mV	P
3	LINE REGULATION	-0.3%~+0.3% (Max)	I/P:36VDC~72VDC O/P:FULL LOAD Ta:25°C	-0.1%~+0.1%	P
4	LOAD REGULATION	-0.5%~+0.5% (Max)	I/P:48VDC O/P:MIN~FULL LOAD Ta:25°C	-0.3%~+0.3%	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	DC VOLTAGE RANGE	36VDC~72VDC (Typ)	I/P:TESTING O/P:FULL LOAD Ta:25°C	27V~72V	P
2	EFFICIENCY	83% (Typ)	I/P:48VDC O/P:FULL LOAD Ta:25°C	83.9%	P
3	DC CURRENT	400mA (Max)	I/P:48VDC O/P:FULL LOAD Ta:25°C	369.5mA	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	160%~250% (Max)	I/P:48VDC O/P:TESTING Ta:25°C	210% Hiccup Mode Reset Auto Recovery	P
2	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P:48VDC O/P:FULL LOAD Ta:25°C	NO DAMAGE Hiccup Mode Reset Auto Recovery	P

ENVIRONMENT TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	TEMPERATURE RISE TEST	1. ROOM AMBIENT BURN-IN : 4HRS I/P:48VDC O/P:FULL LOAD Ta=25°C			P

Position	P/N	TEMP Ta=25°C
CASE	SKE15C-15	46.0°C

SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P:1KVDC/min	I/P-O/P:1KVDC/min Ta:25°C	I/P-O/P:0.02mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P:500VDC Ta:25°C	I/P-O/P:206MΩ NO DAMAGE	P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2004.3.25	SKE15C-15	PASS	T.K.CHENG	MAX LIN